

This listing of claim will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) A conservatory roof comprising:
 - an eaves beam supporting a plurality of rafters;
 - a plurality of panels supported by said rafters;
 - a mounting arm ~~attached to~~ supported by said eaves beam;
 - a plurality of brackets attached to said rafters exteriorly of said eaves beam; and
 - a soffit running along the length of said eaves beam, said soffit supported by said mounting arm and said brackets.
2. (Original) The conservatory roof of claim 1 wherein said soffit is attached to said mounting arm.
3. (Original) The conservatory roof of claim 1 wherein said soffit is attached to said brackets.
4. (Original) The conservatory roof of claim 1 wherein said mounting arm comprises an external trim plate with a horizontal ledge.

5. (Original) The conservatory roof of claim 4 wherein said soffit is attached to said horizontal ledge.
6. (Original) The conservatory roof of claim 1 wherein said brackets include a plurality of horizontal tabs.
7. (Original) The conservatory roof of claim 6 wherein said soffit is attached to said horizontal tabs.
8. (Original) The conservatory roof of claim 1 wherein said brackets are gutter hangers and support a gutter along the length of said eaves beam.
9. (Original) The conservatory roof of claim 1 wherein said soffit protects at least a portion of said rafters and at least a portion of said panels.
10. (Original) The conservatory roof of claim 1 wherein said soffit creates a hollow under at least a portion of said rafters and at least a portion of said panels.
11. (Original) The conservatory roof of claim 1 wherein said soffit is vinyl.

12. (Currently Amended) A conservatory roof comprising:
- an eaves beam supporting a plurality of rafters;
 - a plurality of panels supported by said rafters;
 - a mounting arm ~~attached to~~ supported by said eaves beam, said mounting arm having an external trim plate with a horizontal ledge;
 - a plurality of gutter hangers attached to said rafters exteriorly of said eaves beam, said gutter hangers including horizontal tabs; and
 - a soffit running along the length of said eaves beam, said soffit supported by said horizontal ledge and said horizontal tabs.
13. (Original) The conservatory roof of claim 12 wherein said soffit is attached to said horizontal ledge.
14. (Original) The conservatory roof of claim 12 wherein said soffit is attached to said horizontal tabs.
15. (Original) The conservatory roof of claim 12 wherein said soffit protects at least a portion of said rafters and at least a portion of said panels.
16. (Original) The conservatory roof of claim 12 wherein said soffit creates a hollow under at least a portion of said rafters and at least a portion of said panels.

17. (Original) The conservatory roof of claim 12 wherein said soffit is vinyl.
18. (Original) A conservatory roof system comprising:
- a generally horizontal eaves beam;
 - a sloped roof, said roof having a plurality of sloped panels and a plurality of sloped rafters supporting said panels, said roof supported by said eaves beam, said roof extending exteriorly of said eaves beam whereby an overhang is created; and
 - a generally horizontal soffit paralleling said eaves beam, said soffit connected to said eaves beam and to said roof whereby said eaves beam, said roof and said soffit form a triangularly shaped hollow under said overhang.
19. (Currently Amended) The conservatory roof system of claim 18 further comprising a mounting arm ~~attached to~~ supported by said eaves beam, said mounting arm adapted to support said soffit.
20. (Original) The conservatory roof system of claim 18 further comprising a bracket attached to said roof, said bracket adapted to support said soffit.

21. (New) A conservatory roof system comprising:

a generally horizontal and longitudinal eaves beam;

a sloped roof, the sloped roof having a plurality of sloped rafters attached to, and supported by, the eaves beam, and a plurality of sloped conservatory panels positioned between, and supported by, the rafters, the roof extending exteriorly of the eaves beam whereby an overhang is created, the overhang having an underside portion;

a mounting arm contiguously attached to, and supported by, the eaves beam, the mounting arm having an integral vertical external trim plate with an integral horizontal ledge extending perpendicularly and exteriorly therefrom;

a plurality of gutter hangers attached to the rafters exteriorly of the eaves beam, the gutter hangers having integral horizontal tabs;

a gutter positioned in and supported by the gutter hangers;

a generally horizontal vinyl soffit paralleling and running along the length of the eaves beam, the soffit resting upon and being supported by the horizontal ledge of the mounting arm and the horizontal tabs of the gutter hangers;

wherein a triangularly shaped hollow is formed under the overhang and wherein the soffit protects the underside portion of the overhang portion of the roof.